

# Safety data sheet

# **259 Maintenance Paste**

1. Identification of the substance/preparation and of the company/undertaking

Prepared on: 01-03-2010/ LFH Distributor:

Replaces: 01-02-2008 WoodCare Denmark A/S

Tværvei 6

Product use: Surface treatment of wood indoors 6640 Lunderskov

Tel:99585600 Fax:99585634

**Emergency telephone number: 99585600** 

The emergency telephone is open between 8 a.m. and 4

p.m. on workdays.

**Contact person:Environment Directorate** 

Email: info@ttwoodcare

### 2. Hazards identification

### DSD/DPD-classification

The product shall not be classified as hazardous according to the national classification and labelling rules.

#### Additional information

Prolonged or repeated inhalation of vapours may cause damage to the central nervous system. Risk of self-ignition: Due to the risk of self-ignition it is important that sanding dust and oil wetted cloths are soaked in water and disposed of in a tightly closed container after use

# 3. Composition/information on ingredients

	DSD-Classification	w/w%	
s (petroleum), hydrotreated light	Xn;R65-66	3-5	4
(petroleum), hydrotreated heavy	Xn;R65,R66	25-35	4
roduct.	,		
r	(petroleum), hydrotreated heavy	(petroleum), hydrotreated heavy Xn;R65,R66 roduct.	(petroleum), hydrotreated heavy Xn;R65,R66 25-35

# 4. First aid measures

### Inhalation

Seek fresh air.

### Ingestion

Rinse mouth thoroughly and then drink plenty of water. If vomiting occurs, keep head low so that stomach contents do not enter lungs. Seek medical advice if symptoms persist.

### Skin

Wash skin with soap and water.

### Eyes

Rinse immediately with water (preferably using eye wash) for at least 5 minutes. Open eyes wide. Remove any contact lenses. Seek medical advice if irritation persists.

### Burns

Rinse with water until pain stops. Remove clothes which do not adhere to the body - seek medical advice, if possible continue rinsing until doctor takes over treatment.

# Other information

When obtaining medical advice, show the safety data sheet or label. Symptoms: See section 11.

WoodCare Denmark A/S Tværvej 6, 6640 Lunderskov Tlf.: 99585600 Fax: 99585634, www.woodcaredenmark.com

Prepared on: 01-03-2010/LFH

Replaces: 01-02-2008

# **259 Maintenance Paste**

5. Fire-fighting measures

Extinguish with powder, foam, carbon dioxide or water mist. Do not use water stream, as it may spread the fire. Use water or water mist to cool non-ignited stock. Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases – seek fresh air.

# 6. Accidental release measures

Prevent spillage from entering drains and/or surface water.

# 7. Handling and storage

# Handling

See section 8 for information about precautions for use and personal protective equipment.

#### Storage

Store safely, out of reach of children and not together with food, animal feeding stuffs, medicines, etc. Do not expose to heat (e.g. sunlight). Store frost-free. Keep in tightly closed original packaging.

# 8. Exposure controls/ personal protection

### Precautions for use

Use the product under well-ventilated conditions.

# Respiratory protection

Not required.

### Gloves and protective clothing

Wear protective gloves made of nitrile rubber,

#### Eye protection

Wear safety goggles if there is a risk of eye splash.

### Occupational exposure limits

Ingredients	Exposure limit	Remarks
Naphtha (petroleum), hydrotreated heavy	900 (8h), mg/m3	-

# Control methods

Compliance with the stated occupational exposure limits may be checked by occupational hygiene measurements.

# 9. Physical and chemical properties

State: Paste Flash point: -℃ 61
Density: -g/ml 0,9

# 10. Stability and reactivity

The product is stable when used in accordance with the supplier's directions.

WoodCare Denmark A/S Tværvej 6, 6640 Lunderskov Tlf.: 99585600 Fax: 99585634, www.woodcaredenmark.com

Prepared on: 01-03-2010/LFH

Replaces: 01-02-2008

# **259 Maintenance Paste**

### 11. Toxicological information

#### Acute

### Inhalation

The product releases vapours from organic solvents which may cause lethargy and dizziness. At high concentrations, vapours may cause headaches and intoxication.

#### Ingestion

Ingestion may cause discomfort.

#### Skin contact

Degreases and dries the skin. Repeated exposure may cause skin dryness or cracking.

#### Eve contact

May cause eye irritation.

### Long-term effects

### May cause damage to the central nervous system

Prolonged or repeated inhalation of vapours may cause damage to the central nervous system.

### 12. Ecological information

Avoid discharge to drain or surface water.

# 13. Disposal considerations

Contact the local authorities

# 14. Transport information

The product is not covered by the rules for transport of dangerous goods by road and sea according to ADR and IMDG.

### 15. Regulatory information

Hazard designation: It has been assessed that the product shall not be classified as hazardous according to the national classification and labelling rules.

# Other labelling

# Volatile organic compounds (VOC):

This product contains a maximum of 265 g VOC/L. The limit value is 500 g VOC/L (cat. A/i)

### Chemical safety assessment

Chemical safety assessment has not been performed.

# 16. Other information

### Restrictions on use

### **Training requirement**

No special training is required, but a thorough knowledge of this safety data sheet should be a prerequisite condition.

# Sources used

# Other information

This safety data sheet was prepared from information provided by the supplier about physical/chemical properties and all ingredients in the product.

### Full text of the R-phrases that are stated in section 3.

R65 Harmful: May cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

### Amendments have been made in the following sections

WoodCare Denmark A/S Tværvej 6, 6640 Lunderskov Tlf.: 99585600 Fax: 99585634, www.woodcaredenmark.com (Made in Toxido®) UK